

COMPRESSOR

Type	Twin Rotary
------	-------------

CAPACITY*

Cooling - Min/Norm/Max - kW	1.35/5.27/6.33
-----------------------------	----------------

Heating - Min/Norm/Max - kW	1.41/6.33/7.27
-----------------------------	----------------

POWER INPUT*

Cooling - Min/Norm/Max - A	0.6/6.0/9.0
----------------------------	-------------

Heating - Min/Norm/Max - A	0.8/7.0/11.5
----------------------------	--------------

EER

EER	4.57
-----	------

COP

COP	4.15
-----	------

AIRFLOW RATE

Norm - m ³ /min	31
----------------------------	----

I/S	517
-----	-----

SOUND PRESSURE

Cooling - Norm - dBA	50
----------------------	----

Heating - Norm - dBA	52
----------------------	----

DIMENSIONS

WxHxD - mm	870×655×320
------------	-------------

NET WEIGHT

kg	45.0
----	------

REFRIGERANT

Type	R410A
------	-------

Charge - g	1,700
------------	-------

Additional Charge - g/m	20
-------------------------	----

OPERATION RANGE(OUTDOOR)

Cooling - Min~Max - °C DB	-10~48
---------------------------	--------

Heating - Min~Max - °C WB	-18~18
---------------------------	--------

POWER SUPPLY

ø/V/Hz	1/220-240/50
--------	--------------

POWER SUPPLY CABLE

No.xmm ²	3C×2.5
---------------------	--------

TRANSMISSION CABLE

No.xmm ²	4C×0.75
---------------------	---------

CIRCUIT BREAKER

A	20
---	----

PIPING LENGTH TOTAL

m	50
---	----

PIPING LENGTH PER BRANCH

Max - m	25
---------	----

PIPING ELEVATION DIFFERENCE

IDU-ODU - Max -m	15
------------------	----

IDU-IDU - Max -m	7.5
------------------	-----

PIPING CONNECTION

Liquid - mm(inch)×No.	∅ 6.35 (1/4)×3
-----------------------	----------------

Gas - mm(inch)×No.	∅ 9.52 (3/8)×3
--------------------	----------------
